

7", 8.4", 10" LCD Monitor

Features

- USB or VGA interface available
- Optional resistive touch for 8.4" and 10"
- Easy for installation - one USB cable needed
- Best choice for space limited retail/hospitality settings



OT07



OT84



Wall mount available



Wall Mountable Base (OT84 only)

OT10



VGA interface available



USB Interface available

Specifications

Model	OT07SD	OT07SC	OT84NA	OT84NC	OT10NA	OT10NC
Display Area	153.6 * 86.64 mm		170.4 * 127.8 mm		211.2 * 158.4 mm	
Standard Cabinet Color	Black		Black		Black	
Optimal Resolution	800 * 480 (WVGA)		800 * 600		800 * 600	
Brightness	200 cd/m ² (typ)		230 cd/m ² (typ)	180 cd/m ² (typ)	300 cd/m ² (typ)	180 cd/m ² (typ)
Contrast Ratio	500:1 (typ)		600:1 (typ)		500:1 (typ)	
Response Time	25 ms (typ)		8 ms (typ)		30 ms (typ)	
LCD Viewing Angle(L / R / U / D)	70 / 70 / 50 / 60		75 / 75 / 60 / 70		75 / 75 / 50 / 60	
Tilt Angle	35°(V) / 70°(H) (w/ pole base)		N / A			
Input Video signal connector	Mini Din 8 pins	USB	D-Sub 15 pins	USB B type	D-Sub 15 pins	USB B type
Power consumption	6W	2.5W	6W	2.5W	8W	2.5W
Input Frequency	Horizontal: 31.5-60.2 kHz ; Vertical : 56.3Hz-75Hz					
Power supply	DC 12V +/- 10%	DC 5V +/- 10%	DC 12V +/- 10%	DC 5V +/- 10%	DC 12V +/- 10%	DC 5V +/- 10%
Temperature	Operating : 0°C~40°C ; Storage : -10°C~50°C					
Humidity	Operating : 20%~80% ;Storage : 10%~90%					
Weight	500g (net)		780g (net)		1.2 kgs (net)	
Physical Dimension	192 * 115 * 34.5 mm		199.7 (W) * 197 (H) * 130 (D) mm		239.6 (W) * 227.6 (H) * 160 (D) mm	
Approvals	CE, FCC, BSMI		CE, FCC, BSMI, CCC		CE, FCC, CCC	
Wall Mount	VESA 75 * 75 mm		VESA 75 * 75 mm / key lock hole * 2		VESA 75 * 75 mm	
Touch	N/A		Resistive, Model : OT84TA	N/A	Resistive, Model : OT10TA	N/A
Wall Mounting	Bracket 75 * 75 mm					
Stand Base	Pole + Base		Yes		Yes	

This specification is subject to change without prior notice.

OTEK SYSTEM CO., LTD.

Address: 6F, 30 Sinjhong Rd., Neihu District, Taipei 114, Taiwan Tel: 886-2-7720-1688 Fax: 886-2-7721-2188

http://www.oteksys.com sales@oteksys.com

OT84a-1201

