

POS 345



Smart Design All-in-One POS Terminal

Flytech POS 345 серии является компактным POS терминалом с удобным дизайном. Легкий доступ жесткого диска и материнской платы сокращают время обслуживания. Мощный процессор с низким энергопотреблением делает его виртуальным энергосберегающим решением для использования в любых критических условиях.



Преимущества



Регулировка
наклона 0° ~ 70 °

Различные I/O
порты



iButton-in 2-in-1
MSR



Быстрый доступ к
HDD

Технические характеристики

Model Name	POS 345
Motherboard	C36B
Processor	Intel® Atom™ Processor N270 (1.6GHz L2 512K FSB 533MHz)
Chipset	Intel® 945GSE Express chipset + ICH7M
System Memory	1 x DDR2 DIMM up to 2GB FSB 533MHz
Graphic Memory	Intel® GMA 950 share system memory up to 224MB
LCD Touch Panel	
LCD Size	15" TFT LCD
Brightness	250 cd/m.dz
Resolution	1024x768
Storage Device	
Hard Drive	1 x 2.5" Slim HDD Bay support SATA HDD
Expansion	
Mini PCI-E Slot	1
Rear I/O	
USB Port	4 x USB 2.0
Serial / COM	4 x RJ-45 (COM3 / COM4 with 5V / 12V power)
LAN Port	1 x RJ-45 (10/100/1000Mbps Giga LAN)
VGA	1 (w/o power)
Cash Drawer Port	Support cash drawer 1 x (12V / 24V)
DC Jack	1
Front I/O	
Power Button	1
Power	Adapter (DC 65W, 19V, 3.4A)
Peripheral (Optional)	
MSR	MSR (PS/2) / MSR (PS/2) + iButton (PS/2) / MSR (PS/2) + Finger Print (USB)
VFD	20 x 2 customer display
Certificate	
EMC & Safety	FCC Class A / CE Mark / LVD
Environment	
Operating Temperature	5°C ~ +35°C (41°F ~ +95°F)
Storage Temperature	-20°C ~ 55°C (-4°F ~ 131°F)
Operating Humidity	20% ~ 80% RH non-condensing
Storage Humidity	20% ~ 85% RH non-condensing
Communication	
Wireless LAN	PCI-E wireless LAN card 802.11 b/g, or 802.11 b/g/n
Dimension (W x D x H)	LCD 0° tilt angle: 439 x 284 x 220.7 mm, LCD 70° tilt angle: 439 x 302.2 x 320.8 mm
Weight	6kg (13.2lbs)
OS Supported	Windows® XP, Windows® XP Embedded, Windows® CE, Linux

